

DIRECT COOL
REFRIGERATOR

VitaMagic^{pro}



PRESENTING VITAMAGIC PRO EXPERIENCE THE MAGIC OF AUTO-DEFROST



AUTO-DEFROST

Prevents unnecessary formation of ice, and ensures no manual intervention, zero water spillage and easy removal of items from the freezer.




4X PRECISE COOLING[‡]

VitaMagic Pro is powered by *IntelliSensor* and advanced Microprocessor which gives 4X precise[‡] and uniform cooling with only $\pm 0.5^{\circ}\text{C}$ temperature variation vs. $\pm 2^{\circ}\text{C}$ temperature variation in conventional refrigerators.



UP TO 12 DAYS OF GARDEN FRESHNESS*^⓪

The 6TH SENSE[®] VitaMagic Technology not only preserves nutrients but also maintains an ideal condition for vegetables to stay garden fresh for up to 12 days.



ZEOLITE TECHNOLOGY

Prevents excessive ripening and keeps fruits and vegetables fresh and gives up to 40% longer Vitamin Preservation*^⓪.



12 HOURS** OF MILK PRESERVATION

The Magic Chiller and Laminar Air Flow ensure that milk does not spoil even after 12 hours^⓪ of power cut*.

[‡]Results are based on internal lab tests between NTC sensor & conventional thermostat conducted on select models under standard test conditions and may vary depending on testing conditions.

*Results are based on internal lab testing done on select models under standard test conditions and may vary depending on testing conditions and models. ^⓪Internal lab test conducted on select vegetables.

[^]Product operating at highest cooling setting with restricted usage wherein pH value of milk packet is maintained above 6.4.



VITAMAGIC PRO ROYAL 3 STAR (INVERTER) (215L)

- 6TH SENSE® *Intellifrost* Technology
- Auto-Defrost Technology
- 4X Precise Cooling[‡]
- Up to 12 Days of Garden Freshness[°]
- 40% Longer Vitamin Preservation*
- 12 Hours** of Milk Preservation
- Fast Ice Making^Δ
- Fast Bottle Cooling[¶]
- Microblock Technology
- Zeolite Technology

Available in: Alpha Steel & Wine Hibiscus
Dimensions (WxDxH) (mm): 543 x 618 x 1439



VITAMAGIC PRO PREMIER 3 STAR (INVERTER) (215L)

- 6TH SENSE® *Intellifrost* Technology
- Auto-Defrost Technology
- 4X Precise Cooling[‡]
- Up to 12 Days of Garden Freshness[°]
- 40% Longer Vitamin Preservation*
- 12 Hours** of Milk Preservation
- Fast Ice Making^Δ
- Fast Bottle Cooling[¶]
- Microblock Technology
- Zeolite Technology

Available in: Alpha Steel & Wine Hibiscus
Dimensions (WxDxH) (mm): 535 x 618 x 1326



VITAMAGIC PRO ROYAL 3 STAR (INVERTER) (200L)

- 6TH SENSE® *Intellifrost* Technology
- Auto-Defrost Technology
- 4X Precise Cooling[‡]
- Up to 12 Days of Garden Freshness[°]
- 40% Longer Vitamin Preservation*
- 12 Hours** of Milk Preservation
- Fast Ice Making^Δ
- Fast Bottle Cooling[¶]
- Microblock Technology
- Zeolite Technology
- Stabilizer-free Technology

Available in: Alpha Steel, Neo Dutch & Wine Hibiscus
Dimensions (WxDxH) (mm): 543 x 618 x 1358



VITAMAGIC PRO PREMIER 3 STAR (INVERTER) (200L)

- 6TH SENSE® *Intellifrost* Technology
- Auto-Defrost Technology
- 4X Precise Cooling[‡]
- Up to 12 Days of Garden Freshness[°]
- 40% Longer Vitamin Preservation*
- 12 Hours** of Milk Preservation
- Fast Ice Making^Δ
- Fast Bottle Cooling[¶]
- Microblock Technology
- Zeolite Technology
- Stabilizer-free Operation

Available in: Alpha Steel, Neo Dutch & Wine Hibiscus
Dimensions (WxDxH) (mm): 535 x 618 x 1256



Plasma
INVERTER
TECHNOLOGY^{~ast}
STARTS AT 80V | RELIABILITY TESTED BY VDE FOR 25 YEARS

Auto-connect to
HomeInverter[#]

10 YEAR WARRANTY
1 year comprehensive + 9 year on compressor

STABILISER-FREE OPERATIONS[†]



www.VDEinfo.com
ID: 40048404
Tested by VDE Germany

Results are based on internal lab testing done on select models under standard test conditions and may vary depending on testing conditions and models. [°]Internal lab test conducted on select vegetables. ^ΔProduct operating at highest cooling setting with restricted usage wherein pH value of milk packet is maintained above 6.4. ^{~ast}Plasma treatment on connecting rod only. [#]Auto Connect to ≥ 2.5KVA inverter, each connected to the power switch. [†]Protects the vital components of Refrigerator from power fluctuations. Installing stabiliser becomes needless with this function and Stabiliser is required only if power fluctuation is beyond the range of 80V - 300V for Inverter model and 130V-300V for Non-Inverter model. [‡]Results are based on internal lab tests between NTC sensor & conventional thermostat conducted on select models under standard test conditions and may vary depending on testing conditions. ^{}Results based on internal lab tests done select models in chiller section when operating in FFI setting vs. Mid setting under standard test conditions and may vary depending on testing conditions. [¶]Results based on internal lab tests done select models when operating in FFI setting vs. Mid setting under standard test conditions and may vary depending on testing conditions. ^ΔAbove details are of select model of given technology.